

Symmetrische Racing Spinnakers

S1 LIGHT AIR REACHING



S2 LIGHT AIR RUNNING



S3 MEDIUM AIR REACHING



S4 MEDIUM / HEAVY RUNNING



S5 HEAVY AIR SPINNAKER



Description:

Light Air Reaching Symmetrical Spinnaker. In the past would have been called a VMG spinnaker. Used in winds to light to sail deeper than 110 degrees AWA.

Apparent Wind Speed:

0 - 10 knots

Apparent Wind Angle:

70 - 110 degrees

Materials:

.5 oz. nylon

Description:

Light/Medium Air Running Symmetrical Spinnaker. Full size with big shoulders designed to fly at deep angles.

Apparent Wind Speed:

6 - 18 knots

Apparent Wind Angle:

110 - 170 degrees

Materials:

.6 to .75 oz. nylon

Description:

Medium Air Reaching symmetrical Spinnaker. Wider and deeper shape than the S1. Yet narrower and flatter than the S2 and S4.

Apparent Wind Speed:

10 - 20 knots

Apparent Wind Angle:

70 - 130 degrees

Materials:

.9 to 1.5 oz. nylon

Description:

Medium/Heavy Running Symmetrical Spinnaker. Smaller shoulders than S2, yet still designed to fly at deeper angles.

Apparent Wind Speed:

14 - 30 knots

Apparent Wind Angle:

120 - 170 degrees

Materials:

.9 to 1.5 oz. nylon

Description:

Heavy Air Reaching Asymmetrical Spinnaker. Short on the hoist, or flown from the hounds instead of the masthead on a fractional rig.

Apparent Wind Speed:

20 - 35 knots

Apparent Wind Angle:

90 - 170 degrees

Materials:

1.5 to 2.2 oz. nylon



Waardwei 7 8754 HB Makkum 0515-231738 info@uk-devriessails.nl

www.uk-devriessails.nl